

THE CORPORATION OF THE CITY OF BRAMPTON

BY-LAW

To amend Comprehensive Zoning By-law 270-2004, as amended

The Council of the Corporation of the City of Brampton, in accordance with the provisions of the *Planning Act, R.S.O. 1990, c.P. 13,* hereby ENACTS as follows:

- 1. By-law 270-2004, as amended, is hereby further amended:
 - (1) By changing Schedule A thereto, the zoning designation of the lands as shown outlined on Schedule A to this by-law:

From:	То:
"AGRICULTURAL (A)" & "AGRICULTURAL – 1520 (A-1520)"	RESIDENTIAL SINGLE DETACHED F – 11.0 – SECTION AAA (R1F – 11.0 – AAA)
	RESIDENTIAL TOWNHOUSE E – 6.1 – SPECIAL SECTION BBB (R3E – 6.1 – BBB)
	RESIDENTIAL SINGLE DETACHED F – 9.15 – SECTION CCC (R1F – 9.15 – CCC)
	RESIDENTIAL SINGLE DETACHED F – 13.7 – SECTION DDD (R1F – 13.7 – DDD)

RESIDENTIAL SINGLE DETACHED F – 15.0 – SECTION EEE (R1F – 15.0 – EEE)
RESIDENTIAL TOWNHOUSE A – R3C – SECTION FFF (R3C – FFF)
OPEN SPACE ZONE (OS)
FLOODPLAIN (F)

(2) By adding the following Sections:

"AAA The lands designated R1F - 11.0 - AAA on Schedule A to this bylaw:

AAA.1 Shall only be used for the purposes permitted in an R1F – 11.0 zone.

AAA.2 Shall be subject to the following requirements and restrictions:

(2) Minimum Lot Width	Interior Lot – 11.0 metres
	Corner Lot – 13.0 metres
(3) Minimum Front Yard	a) 3.0 metres;
	b) 6.0 metres to a garage door;
	 c) the main wall of a dwelling may encroach into the front yard to within 1.0 metres of a daylight rounding or triangle;
	 a porch and/or balcony with or without foundation or cold cellar may encroach 2.0 metres into the minimum front yard with an additional 0.25 metre encroachment for steps;
	 e) a porch and/or balcony with or without foundation or cold cellar including steps, eaves and cornices may encroach into the front yard to within 0.0 metres of a daylight rounding or triangle;
	 f) a bay window, bow window, box window with or without foundation or cold cellar may encroach 1.0

		metres into the minimum front yard; and
	g)	a bay window, bow window or box window with or without foundation or cold cellar including eaves and cornices may encroach into the front yard to within 0.0 metres of a daylight rounding or triangle;
(4) Minimum Exterior Side Yard	a)	3.0 metres and 1.2 metres were an exterior side yard abuts a public or private lane;;
	b)	6.0 metres to a garage door facing the exterior side yard for corner lots;
	c)	the main wall of a dwelling may encroach into the exterior side yard to within 1.0 metres of a daylight rounding or triangle;
	d)	a porch and/or balcony with or without foundation or cold cellar and chimney may encroach 2.0 metres into the minimum exterior side yard with an additional 0.25 metre encroachment for steps
	e)	a porch and/or balcony with or without foundation or cold cellar including steps, eaves and cornices may encroach into the exterior side yard to within 0.0 metres of a daylight rounding or triangle;
	f)	a bay window, bow window or box window with or without foundation may encroach 1.0 metre into the minimum exterior side yard and within 0.0 metres of a daylight rounding or triangle
(5) Minimum Rear Yard Depth	a)	7.0 metres for an interior lot;
	b)	6.0 metres when a rear yard abuts an interior side yard;
	c)	6.0 metres when a rear yard abuts an Open Space, Floodplain or Institutional zone;

	d)	3.0 metres for a corner lot provided that not less than 50% of the unit width is setback 6.0 metres from the rear lot line;
	e)	0.6 metres to the side wall of a garage, where access to the garage is from the exterior side yard for lots equal to or greater than 13.4 metres;
	f)	A deck may encroach into the rear yard to within 3.0 metres of the rear lot line;
	g)	Open roofed porches and or uncovered terraces may encroach in to the rear yard to within 3.0 metres of the rear lot line
	h)	a bay window, bow window or box window with or without foundation may encroach 1.0 metres into the minimum rear yard;
(6) Minimum Interior Side Yard	a)	1.2 metres on one side and 0.6 metres on the other side provided that the combined total for each interior lot is 1.8 metres;
	b)	Interior side yards between two lots can be paired at 0.6 metres per paired lots, and or 1.2 metres and 0.6 metres per paired lots and or at 1.2 metres and 1.2 metres per paired lots;
	c)	1.2 metres where the side yard abuts a public walkway or a non-residential zone; and
	d)	0.6 metres for a corner lot abutting another interior lot with a side yard of 0.6 metres or 1.2 metres, for a minimum total of 1.2 metres between buildings;
	e)	1.2 metres for semi-detached units for the opposite side of the attached wall.

(7) For corner lots, either the exterior side yard or interior side yard shall maintain a minimum 1.2 metres regardless of permitted encroachments.		
(8) Maximum Building Height	12 metres	
(9) The following provisions shall apply to garages:	 a) No garage may project more than 1.5 metres beyond the porch or front wall of a dwelling; 	
	 b) the maximum cumulative garage door width for lots, with a lot width equal to or greater than 11.6 metres but less than 12.5 metres shall be 5.0 metres; 	
	c) the maximum cumulative garage door width for lots, with a lot width equal to or greater than 12.5 metres but less than 15.0 metres shall be 5.5 metres;	
	 d) the garage door width restriction does not apply to a garage door facing the exterior lot line; 	
	 e) minimum interior garage dimension of single vehicle garage shall measure 6.0 metre interior length x 3.1 metre minimum interior width. 	
	 f) No encroachment shall be permitted into a required parking space within a garage, except for one step (2 risers) into the minimum garage length; 	
(10) The Following shall apply to a bay, bow or box window:	a) notwithstanding Section 6.13 Table 6.13.A the maximum width of a bay, bow or box window with or without foundation shall be 4.5 metres;	
	 b) notwithstanding Section 6.13 Table 6.13.A the maximum depth of a bay, bow or box window with or without foundation shall be 1.0 metres; 	
	c) a bay, bow or box window with a maximum depth of 0.6 metres does	

not need to contain side windows; and
 a bay, bow or box window with a depth greater than 0.6 metres up to a maximum depth of 1.0 metres does need to contain side windows;

(3) By adding the following Sections:

"BBB The lands designated R3E - 6.1 - BBB on Schedule A to this bylaw: BBB.1 Shall only be used for the purposes permitted in an R3E - 6.1 - BBB zone.

a) Dwelling, Street Townhouse

BBB.2 Shall be subject to the following requirements and restrictions:

(1) Minimum Lot Area	Interior Lot: 165 square metres
	Corner Lot: 240 square metres
	End Lot: 195 square metres
(2) Minimum Lot Width	Interior Lot: 6.1 metres
	Corner Lot: 8.9 meters
	End Lot: 7.3 metres
(3) Minimum Front Yard	a) 3.0 metres;
	b) 6.0 metres to the front of the garage;
	 c) the main wall of a dwelling may encroach into the front yard to within 1.0 metres of a daylight rounding or triangle;
	 a porch and/or balcony with or without foundation or cold cellar may encroach 2.0 metres into the minimum front yard with an additiona 0.25 metres encroachment for steps;
	 e) a porch and/or balcony with or without foundation or cold cellar including steps, eaves and cornices may encroach into the front yard to

		 within 0.0 metres of a daylight rounding or triangle; f) a bay window, bow window, box window with or without foundation or cold cellar may encroach 1.0 metres into the minimum front yard; and g) a bay window, bow window or box window with or without foundation or cold cellar including eaves and cornices may encroach into the front yard to within 0.0 metres of a daylight rounding or triangle;
	(4) Minimum Exterior Side Yard	a) 3.0 metres
		 b) 6.0 metres to a garage door facing the exterior side yard for corner lots;
		 c) the main wall of a dwelling may encroach into the exterior side yard to within 1.0 metres of a daylight rounding or triangle;
		 a porch and/or balcony with or without foundation or cold cellar and chimney may encroach 2.0 metres into the minimum exterior side yard with an additional 0.25 metre encroachment for steps;
		 e) a porch and/or balcony with or without foundation or cold cellar including steps, eaves and cornices may encroach into the exterior side yard to within 0.0 metres of a daylight rounding or triangle;
		 f) a bay window, bow window or box window with or without foundation or cold cellar may encroach 1 .0 metres into the minimum exterior side yard and within 0.0 metres of a daylight rouding or triangle;;
	(5) Minimum Rear Yard Depth	a) 6.0 metres for an interior lot;
		b) 3.0 metres for a corner lot provided that not less than 50% of the unit

	width is setback 5.0 metres from the
	rear lot line;
	c) 3.5 metres to a deck off the main floor; and
	d) a bay window, bow window or box window with or without a foundation and a porch or cold cellar may encroach 1.0 metres into the year yard.
(6) Minimum Interior Side Yard	 a) 1.2 metres when abutting side lot line coincides with two exterior walls;
(7) Maximum Building Height	14 metres
(8) Minimum Dwelling Unit Width	6.0 metres
(9) The following provisions shall apply to garages:	 a) No garage may project more than 1.5 metres beyond the porch or front wall of a dwelling;
	 b) minimum interior garage dimension of single vehicle garage shall measure 6.0 metre interior length x 3.1 metre minimum interior width.
(10) The Following shall apply to a bay, bow or box window:	e) notwithstanding Section 6.13 Table 6.13.A the maximum width of a bay, bow or box window with or without foundation shall be 4.5 metres;
	f) notwithstanding Section 6.13 Table 6.13.A the maximum depth of a bay, bow or box window with or without foundation shall be 1.0 metres;
	 g) a bay, bow or box window with a maximum depth of 0.6 metres does not need to contain side windows; and
	 h) a bay, bow or box window with a depth greater than 0.6 metres up to a maximum depth of 1.0 metres does need to contain side windows;

(11) Notwithstanding Section 10.13.2, front to rear pedestrian access through the dwelling unit does not need to be provided.

(3) By adding thereto, the following sections:

"CCC The lands designated R1F – 9.15 – CCC on Schedule A to this by-law:

CCC.1 Shall only be used for the purposes permitted in an R1F – 9.15 zone.

CCC.2 Shall be subject to the following requirements and restrictions:

(1) Minimum Lot Width	Interior Lot: 9.15 metres
	Corner Lot: 10.9 square metres
(2) Minimum Front Yard Depth	a) 3.0 metres;
	 b) 6.0 metres to a garage door facing the front lot line;
	c) the main wall of a dwelling may encroach into the front yard to within 1.0 metre of a daylight rounding/triangle;
	 a porch and/or balcony with or without foundation or cold cellar may encroach 2.0 metres into the minimum front yard;
	e) a porch and/or balcony with or without foundation or cold cellar including steps eaves and cornices may encroach into the front yard to within 0.0 metres of a daylight rounding/triangle;
	f) a bay window, bow window, box window with or without foundation or cold cellar may encroach 1.0 metre into the minimum front yard; and
	 g) a bay window, bow window or box window with or without foundation or cold cellar including eaves and cornices may encroach into the front yard to within 0.0 metres of a daylight rounding/triangle;

	(3) Minimum Exterior Side Yard	a) 3.0 metres;
		b) 1.2 metres where the exterior side yard abuts a public or private lane;
		 c) 6.0 metres to a garage door facing the exterior side yard for corner lots;
		 d) the main wall of a dwelling may encroach into the exterior side yard to within 1.0 metres of a daylight rounding/triangle;
		e) a porch and/or balcony with or without foundation or cold cellar and chimney may encroach 2.0 metres into the minimum exterior side yard;
		 f) a porch and/or balcony with or without foundation or cold cellar including eaves and cornices may encroach into the exterior side yard to within 0.0 metres of a daylight rounding/triangle;
		 g) a bay window, bow window or box window with or without foundation and a porch or cold cellar including eaves and cornices may encroach into the exterior side yard to within 0.0 metres of a daylight rounding/triangle;
		 h) a bay window, bow window or box window with or without foundation or cold cellar may encroach 1.0 metres into the minimum exterior side yard; and,
	(4) Minimum Rear Yard Depth	a) 7.0 metres for an interior lot;
		 b) 6.0 metres when a rear yard abuts an interior side yard OR when a lot is adjacent to a SWM Pond, Open Space, School, Park;
		c) 3.0 metres for a corner lot provided that not less than 50% of the unit width is setback 6.0 metres from the rear lot line;

	d) 3.5 metres to a deck off the main floor;
	e) 0.6 metres to the side wall of a garage, where access to the garage is from the exterior side;
	f) 4.5 metres for open roofed porches and or uncovered terraces; and
	g) a bay window, bow window or box window with or without foundation and a porch or cold cellar may encroach 1.0 metre into the minimum rear yard;
(5) Minimum Interior Si	de Yard a) 1.2 metres on one side and 0.6 metres on the other side provided that the combined total for each interior lot is 1.8 metres;
	b) interior side yards between two lots can be paired at 0.6 metres per paired lots, and or 1.2 metres and 0.6 metres per paired lots and or at
	c) 1.2 metres and 1.2 metres per paired lots;
	d) 1.2 metres where the side yard abuts a public walkway or a non- residential zone; and
	e) 0.6 metres for a corner lot abutting another interior lot with a side yard of 0.6 metres or 1.2 metres , for a minimum total of 1.2 metres between buildings;
	g) A porch and/or balcony with or without foundation or cold cellar may encroach 0.5 metres into the minimum required 1.2 metre Interior Side Yard;
(6) Maximum Building	Height 12 metres

(7) The following provisions shall apply to garages:	 a) No garage may project more than 1.5 metres beyond the porch or front wall of a dwelling;
	b) the maximum cumulative garage door width shall be 3.7 metres;
	c) wall of a dwelling.minimum interior garage dimension of single vehicle garage shall measure 6.0 metre interior length x 3.1 metre minimum interior width.
(8) The Following shall apply to a bay, bow or box window:	 a) Notwithstanding Section 6.13 Table 6.13.A the maximum width of a bay, bow or box window with or without foundation shall be 4.5 metres;
	b) Notwithstanding Section 6.13 Table 6.13.A the maximum depth of a bay, bow or box window with or without foundation shall be 1 .0 metres;
	c) A bay, bow or box window with a maximum depth of 0.6 metres does not need to contain side windows; and,
	 A bay, bow or box window with a depth greater than 0.6 metres up to a maximum depth of 1.0 metres does need to contain side windows.

(3) By adding thereto, the following sections:

- "DDD The lands designated R1F 13.7 DDD on Schedule A to this bylaw:
- DDD.1 Shall only be used for the purposes permitted in an R1F 13.7 zone and
- DDD.2 Shall be subject to the following requirements and restrictions:

(1) Minimum Lot Width	Interior Lot – 13.7 metres

(4) Minimum Front Yard	a)	3.0 metres;
	b)	6.0 metres to a garage door facing the front lot line;
	c)	the main wall of a dwelling may encroach into the front yard to within 1.0 metres of a daylight rounding/triangle;
	d)	a porch and/or balcony with or without foundation or cold cellar may encroach 2.0 metres into the minimum front yard;
	e)	a porch and/or balcony with or without foundation or cold cellar including eaves and cornices may encroach into the front yard to within 0.0 metres of a daylight rounding/triangle;
	f)	a bay window, bow window or box window with or without foundation or cold cellar may encroach 1.0 metres into the minimum front yard; and,
	g)	a bay window, bow window or box window with or without foundation or cold cellar including eaves and cornices may encroach into the front yard to within 0.0 metres of a daylight rounding/triangle.
(5) Minimum Exterior Side Yard	a)	3.0 metres;
	b)	1.2 metres where the exterior side yard abuts a public or private lane;
	c)	6.0 metres to a garage door facing the exterior side yard for corner lots;
	d)	the main wall of a dwelling may encroach into the exterior side yard to within 1.0 metres of a daylight rounding/triangle;
	e)	a porch and/or balcony with or without foundation or cold cellar and chimney may encroach 2.0

		metres into the minimum exterior side yard;
	f)	a porch and/or balcony with or without foundation or cold cellar including eaves and cornices may encroach into the exterior side yard to within 0.0 metres of a daylight rounding/triangle;
	g)	a bay window, bow window or box window with or without foundation and a porch or cold cellar including eaves and cornices may encroach into the exterior side yard to within 0.0 metres of a daylight rounding/triangle;
	h)	a bay window, bow window or box window with or without foundation or cold cellar may encroach 1.0 metres into the minimum exterior side yard; and,
	i)	For corner lots with a 1.2 metres exterior side yard adjacent to a lane, the maximum encroachment of any type into an exterior side yard shall be 0.5 metres.
(6) Minimum Rear Yard Depth	a)	7.5 metres
	b)	3.0 metres for a corner lot provided that not less than 50% of the unit width is setback 6.0 metres from the rear lot line;
	c)	3.5 metres to a deck off the main floor;
	d)	0.6 metres to the side wall of a garage, where access to the garage is from the exterior side yard for lots equal to or greater than 13.4 metres;
	e)	4.5 metres for open roofed porches and or uncovered terraces; and
	f)	a bay window, bow window or box window with or without foundation and a porch or cold cellar may

1			
			encroach 1.0 metres into the minimum rear yard;
	(7) Minimum Interior Side Yard	a)	1.2 metres on one side and 0.6 metres on the other side provided that the combined total for each interior lot is 1.8 metres;
		b)	Interior side yards between two lots can be paired at 0.6 metres per paired lots, and or 1.2 metres and 0.6 metres per paired lots and or at
		c)	1.2 metres and 1.2 metres per paired lots;
		d)	1.2 metres where the side yard abuts a public walkway or a non- residential zone; and
		e)	0.6 metres for a corner lot abutting another interior lot with a side yard of 0.6 metres or 1.2 metres, for a minimum total of 1.2 metres between buildings;
		f)	A porch and/or balcony with or without foundation or cold cellar may encroach 0.5 metres into the minimum required 1.2 metre Interior Side Yard;
	(8) Maximum Building Height		12 metres
	(9) The following provisions shall apply to garages:	a)	No garage may project more than 1.5 metres beyond the porch or front wall of a dwelling;
		b)	the maximum cumulative garage door width for lots, with a lot width equal to or greater than
		c)	12.5 metres but less than 14.0 metres shall be
		d)	5.5 metres;
		e)	for lots 14.0 metres wide or greater, the maximum cumulative interior garage width shall be 6.4 metres or

	50% of the dwelling unit width whichever is greater;
	 f) the garage door width restriction does not apply to a garage door facing the exterior lot line; and
	 g) the interior garage width, as calculated 3.0 metres from the garage opening shall be a maximum 0.9 metres greater than the maximum cumulative garage door width permitted on the lot;
	 h) minimum interior garage dimension of single vehicle garage shall measure 6.0 metre interior length x 3.1 metre minimum interior width.
(10) The Following shall apply to a bay, bow or box window:	 a) notwithstanding Section 6.13 Table 6.13.A the maximum width of a bay, bow or box window with or without foundation shall be 4.5 metres;
	 b) notwithstanding Section 6.13 Table 6.13.A the maximum depth of a bay, bow or box window with or without foundation shall be 1.0 metres;
	c) a bay, bow or box window with a maximum depth of 0.6 metres does not need to contain side windows; and
	 a bay, bow or box window with a depth greater than 0.6 metres up to a maximum depth of 1.0 metres does need to contain side windows;

(4) By adding thereto, the following sections:

"EEE	The lands designated R1F – 15.0 – EEE on Schedule A to this by-la	aw:
------	-------------------------------------------------------------------	-----

- EEE.1 Shall only be used for the purpose permitted in an R1F 15.0 zone; and,
- EEE.2 Shall be subject to the following requirements and restrictions:

(1) Minimum Lot Width	Interior Lot: 15.0 metres
(2) Minimum Front Yard	a) 3.0 metres;
	 b) 6.0 metres to a garage door facing the front lot line;
	 c) The main wall of dwelling may encroach into the front yard to within 1.0 metres of a daylight rounding or triangle
	 A porch and/or balcony with or without a foundation may encroach 2.0 metres into the minimum front yard;
	e) A bay window; bow window or window with or without a foundation or cold cellar may encroach 1.0 metre into the minimum front yard;
	 f) a porch and/or balcony with or without foundation or cold cellar including steps eaves and cornices may encroach into the front yard to within 0.0 metres of a daylight rounding or triangle;
	g) a bay window, bow window, box window with or without foundation or cold cellar may encroach 1.0 metre into the minimum front yard; and
	 h) a bay window, bow window or box window with or without foundation or cold cellar including eaves and cornices may encroach into the front yard to within 0.0 metres of a daylight rounding or triangle;
(3) Minimum Exterior Side Yard	a) 3.0 metres and 1.2 metres were an exterior side yard abuts a public or private lane;
	 b) 6.0 metres to a garage door facing the exterior side yard for corner lots;
	 c) the main wall of a dwelling may encroach into the exterior side yard

	to within 1.0 metres of a daylight rounding;
	 a porch or balcony with or without foundation or cold cellar may encroach 2.0 metres into the exterior side yard;
	e) a porch and/or balcony with or without foundation or cold cellar may encroach into the exterior side yard to within 0.0 metres of a daylight rounding;
	 f) a bay window, bow widow or box window with or without foundation may encroach 1.0 metres into the exterior side yard;
(4) Minimum Rear Yard Depth	a) 7.5 metres for an interior lot;
	b) 3.0 metres for a corner lot provided that not less than 50% of the unit width is setback 6.0 metres from the rear lot line;
	c) 3.5 metres to a deck off the main floor;
	d) 0.6 metres to the side wall of a garage, where access to the garage is from the exterior side yard for lots equal to or greater than 13.4 metres;
	e) 4.5 metres for open roofed porches and or uncovered terraces; and
	 f) a bay window, bow window or box window with or without foundation and a porch or cold cellar may encroach 1.0 metres into the minimum rear yard;
(5) Minimum Interior Side Yard Width	a) 1.2 metres on one side and 0.6 metres on the other side provided that the combined total for each interior lot is 1.8 metres;
	b) Interior side yards between two lots can be paired at 0.6 metres per paired lots, and or 1.2 metres and 0.6 metres per paired lots and or at 1.2 metres and 1.2 metres per paired lots;

	 c) 1.2 metres where the side yard abuts a public walkway or a non-residential zone; and d) 0.6 metres for a corner lot abutting another interior lot with a side yard of 0.6 metres or 1.2 metres, for a minimum total of 1.2 metres between buildings; e) A porch and/or balcony with or without foundation or cold cellar may encroach 0.5 metres into the minimum required 1.2 metre Interior Side Yard;
(6) Maximum Building Height	12.0 metres
(7) The following provisions shall apply to garages:	a) the maximum cumulative garage door width for lots, with a lot width equal to or greater than 12.5 metres but less than 14.0 metres shall be 5.5 metres;
	 b) for lots 14.0 metres wide or greater, the maximum cumulative interior garage width shall be 6.4 metres or 50% of the dwelling unit width whichever is greater;
	 c) the garage door width restriction does not apply to a garage door facing the exterior lot line; and
	 d) the interior garage width, as calculated 3.0 metres from the garage opening shall be a maximum 0.9 metres greater than the maximum cumulative garage door width permitted on the lot;
	 e) minimum interior garage dimension of single vehicle garage shall measure 6.0 metre interior length x 3.1 metre minimum interior width.
(8) The Following shall apply to a bay, bow or box window:	a) notwithstanding Section 6.13 Table 6.13.A the maximum width of a bay, bow or box window with or without foundation shall be 4.5 metres;

b)	notwithstanding Section 6.13 Table 6.13.A the maximum depth of a bay, bow or box window with or without foundation shall be 1.0 metres;
c)	a bay, bow or box window with a maximum depth of 0.6 metres does not need to contain side windows; and
d)	a bay, bow or box window with a depth greater than 0.6 metres up to a maximum depth of 1.0 metres does need to contain side windows;

- FFF The lands designated R3C Section FFF on Schedule A to this by-law:
- FFF.1 Shall only be used for the purposes permitted in a R3C zone;
- FFF.2 Shall be subject to the following requirements and restrictions:

(1) Minimum Lot Area	100 square metre per dwelling unit
(2) Minimum Yard Setback for Principle Building:	a) The front wall of a dwelling unit: 2.0 metres to a public or private road.
	 b) The rear wall of a dwelling unit: 2.0 metres to a public or private road;
	 c) a porch and/or balcony with or without a foundation may encroach 1.0 metres into the minimum front yard;
	 d) A bay window, bow window or windows with or without a foundation or cold cellar may encroach 1.0 metre into the minimum front yard;
	 e) a porch and/or balcony with or without foundation or cold cellar including steps eaves and cornices may encroach

		into the front yard within 0.0 metres of a daylight
		rounding/tringles;
	(3) Minimum Exterior Side Yard	a) 1.2 metres;
		 b) 0.6 metres abutting a parking area and public walkway
	(4) Minimum interior side yard	 a) 1.2 metres when abutting side lot line coincides with two exterior walls;
		 b) 0.0 metres when abutting side lot line coincides with a common wall between two dwellings;
		c) 0.5 metres into the 1.2 metres interior side yard for a bay window, or box window with or with foundation or cold cellar; and
		 d) 0.7 metres to a bay, bow or box window with or without foundations or cold cellar;
	(5) Maximum building height	13 metres
	(6) The following provisions shall apply to garages:	 a) The maximum cumulative garage door width shall be 5.6 metre.
		 b) minimum interior garage dimension of single vehicle garage shall measure 6.0 metre interior length x 3.1 metre minimum interior width.
	(7) Minimum landscaped open space	No requirement
	(8) Minimum Amenity Area	a) 3.5 square metres shall be provided either on a balcony/uncovered terrace on the second or third floor, or at ground level.
	(9) Air conditioning units are permit uncovered terrace.	

(10) Notwithstanding Section 10. access through the dwelling un	.13.2, front to rear yard pedestrian it is not required.
• •	.9.1.B 1), the minimum driveway shall not exceed the width of the
(12) Section 10.9.1.4 shall not ap	oply.
yard – 1.2 metres.	in the front yard and in the rear
	ninium Laneway Aisle Width: 6.0 ding access to a parking space.
(15) No accessory structure shal yard.	Il be erected in the front and rear
(16) Minimum Visitor Parking Sp	aces: 0.25 spaces per unit.
(17) Setbacks to TransCanada pipeline right-of-way:	 a) A minimum setback of 7.0 m shall be required from any part of a principal building or structure from the edge of the TransCanada pipeline right-of way. b) A minimum setback of 3.0 m shall be required from any part of an accessory building or accessory structure from the edge of the TransCanada pipeline right-of-way.
	 c) A minimum setback of 7.0 m from the nearest portion of a TransCanada pipeline right-of- way shall also apply to any minimum required parking area or loading area, including any minimum required parking space, loading space, stacking space, bicycle parking space, and any associated aisle or driveway.

